

FLAT BED - METAL LASER SOLUTION

LS100 Ex Fibre



GRAVOGRAPH

A COMPACT FIBRE LASER SOLUTION
WITH EXTENDED CAPABILITIES

LS100 Ex Fibre*

FINE AND HIGH-CONTRAST LASER MARKING.
ERGONOMIC AND RELIABLE MACHINE.

Ideal for Industrial parts marking and identification plates. Accurate cutting of thin metallic parts, engraving gifts, jewellery, trophies and awards, pens, tankards.

- Excellent results on steel, stainless steel, titanium, aluminum, carbide, silver, gold, brass, ceramics, ABS.
- The LS100EX Fibre solution specializes in engraving on a full range of metals - no need to apply special consumables to the surface. Excellent results on ABS plastics, etc.
- Easy to set-up in an industrial or commercial environment. Its 610 x 305 mm (24 x 12 in.) marking area is ideal for series of small objects, large objects and matrices: productivity guaranteed.
- The machine design maximizes user comfort: easy-access, front opening makes loading and adjusting jobs effortless. Its point n' shoot function allows for quick, error-free set-up. The autofocus feature ensures precise engraving results.
- An ergonomic LCD control panel and short-cut functions streamline workflow tanks to the selection of the job to engrave in the queuing.
- A range of fumes exhausts to preserve the working environment in perfect condition.
- Optional accessories extend the LS100Ex Fibre's capabilities and your business opportunities: cylindrical attachment, vacuum table to secure thin materials in position, plus a full range of lenses for high definition engraving.
- Driven by LaserStyle, professional interface, Graphic level delivered as standard with the Fibre solution. Its makes job creation easier than ever. Marking parameters are saved with each job design for future use.



■ ENGRAVING CAPACITIES

Engraving area: 610 x 305mm
Z-clearance: 250 mm
Maximum item size: 760 x 330 x 250 mm
Maximum item weight: 20 Kg
Raster Speed: 1,50 m/s

■ LASER SOURCE

Pulsed fibre - 1,06 µm
Power: 20W
Security: CDRH Class II

■ INTERFACE SOFTWARE

LASERSTYLE GRAPHIC as standard

■ DIMENSIONS & UTILITIES

Overall machine size: 1025 x 725 x 450 mm
Net weight: 75 kg

■ OPTICS

- 3.0 in. lens as standard
- 2.0 - 4.0 in. optional

■ MACHINE SUPPORT

Floor stand support which can integrate the ES device

■ FUMES EXHAUSTS

- ES10, ES30 (floor stand devices)
- LE150HP (integrated device)

■ WORKING TABLES

- Vacuum table for thin material
- Floating pin tables
- Honeycomb table

■ CYLINDRICAL ATTACHMENT

- Diam. 3 - 130 mm
- Max. length item 500 mm



Do not use to process
PVC based material.
Never leave the machine
operating unattended.

 **GRAVOGRAPH**

et varemærke fra GravoTech Marking

Gravograph dk A/S
Industrisvinget 9
4030 Tune
Tel: 46 13 96 00
Fax: 46 13 95 02
gravo@gravograph.dk
www.gravograph.dk